

25/28kV Standoff Bushing

By Hubbell Power Systems
Catalog # [228SB](#)

Load Break Insulated Parking Bushing, 200 Amp, 25/28 kV.



Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. 592 requirements
- Interchangeable with other products meeting the same requirements
- Fully shielded, insulated and submersible

General

Catalog Number	228SB
Type	200Amp Load Break
UPC	096359647812

Dimensions

Dimensions	9.500 in x 7.00 in x 4.00 in
Height	4 in
Length	9.5 in
Weight	3.51 lb
Width	7 in

Electrical Ratings

AC Withstand Voltage (1 min)	40 kV
------------------------------	-------

Basic Impulse Level	125 kV
Corona Extinction (3pC)	19 kV
Current Rating	200 A
kV Class	25/28 kV

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
--------------------------	---

Logistics

Pallet Quantity	192
Standard Package	1

Product Assets

- [Catalogs - Cable Accessories](#)
- [Installation Manuals - 200A, 15kV & 25kV Class Insulated Parking Bushing](#)
- [Sales Drawings - 28kV Insulated Parking Bushing](#)
- [SDS - VERSILUBE G661 SILICONE COMPOUND](#)
- [Specifications - 228SB](#)
- [Video - Grease Best PRactices](#)